

## TEKNİK ÖZELLİKLER








- Çift devirli motor sayesinde malzeme özelliklerine göre en uygun devri seçebilme
- Her iki yöne doğru 45° 'ye kadar hassas açılı kesim imkanı
- Kabin içinde bulunan soğutma sıvısı tankı ve motoru sayesinde testerenin soğutulabilmesi ve çıkan talaşların kesim yüzeyinden süratle uzaklaştırabilmesi
- Özel dayama mekanizması ile bir defa ayarlandıktan sonra parçaların aynı uzunlukta standart olarak kesilebilmesi

## CE Normlarına Uygun Güvenlik Sistemi

- Testereye karşı maksimum koruma sağlayan hareketli muhafaza
- 24 V düşük gerilim güvenlik sistemi
- Acil stop butonu
- Kullanım kılavuzu

## Opsiyonel Aksesuarlar

Malzeme destekleme sehpası

		W=600 H=1400 L=1100					
		185	3~	102	1-1,3	45/90	120



Pnömatik Mengeneli Manuel  
Manual With Pneumatic Vice

# V 275 T

## TECHNICAL FEATURES

- 2 Speed main motor
- Adjustable bar stop to make cuts of the same length
- 45° right to 45° left cutting
- Double head return spring
- Coolant tank with box to collect chips and electric pump for blade lubrication and cooling
- Gearbox reduction in oil bath with adjustable bearings








## Safety Equipments According To The CE Standards

- Start push button inside the handle of the control lever (Low voltage 24 V)
- Emergency stop button
- Blade safety guard
- Instructions manual

## Optional Accessories

Material support roller



					D 275
	85	70	95x60		d 32
	70	60	70x55		i 10
					f 63